

Glass GS10

Technical Data

GlassType/Application	Transition glass. SCHOTT glass no. 8213			
Physical Data (approx. value)	Coefficient of mean linear thermal expansion			
	$\alpha(20^{\circ}\text{C}; 300^{\circ}\text{C})$ (ISO 7991)	1.25	10^{-6}K^{-1}	
	Glass temperature at viscosity η in dPa·s			
	$10^{14.7}$ (strain point) (ISO 7884-4)	635	$^{\circ}\text{C}$	
	$10^{13.2}$ (annealing point) (ISO 7884-4)	725	$^{\circ}\text{C}$	
	$10^{7.6}$ (softening point) (ISO 7884-3)	1195	$^{\circ}\text{C}$	
	10^4 (working point) (ISO 7884-3)	1710	$^{\circ}\text{C}$	
	Density (DIN 66137-2)	2.17	g/cm^3	
	Log of the electric volume resistivity ($\Omega \cdot \text{cm}$)			
	at 250°C	10.5		
	at 350°C	8.9		
	t_{k100}	420	$^{\circ}\text{C}$	
Chemical Composition (components in approx. weight %)	SiO ₂	B ₂ O ₃	Al ₂ O ₃	BaO Fe ₂ O ₃
	85	10	4.5	0.5 <0.1
	The heavy metal content for the elements lead, cadmium, mercury and hexavalent chromium is below 100 ppm.			